



Technical Data Sheet

Description

ACCURATE[™]4012N is a free-flowed and water-soluble white powder, produced by spray and dry process mostly based on Ethylene-Acetate(VAE). It dissolves in water easily and forms the membrane has excellent performance in increasing the cohesion, adhesion and flexibility of various sunstrates.

Product Specifications

GRADE	ACCURATE™4012N
Chemical name	Vinyl Acetate Ethylene Redispersible Powder
Solid Content	97-99%
Ash content(1000℃)	12±2%
Packing density (g/l)	400-600
pH value	6.0-8.0
Particle size	90% pass 100 mesh
TG(℃)	15±5
Min Film-forming Temperature	5°C
Flexibility	Rigid

Recommend Applications

Tile adhesive Wall putty Self-leveling mortar Adhesive mortar for EIFS

Surface mortar for EIFS

Typical Properties

Dissolves in water easily and forms emulsion quickly
Prolong the open time
Improve the workability
Strong bonding strength

Packing & Storage

- 1. Multi layer paper bag with inner PE film
- 2. 25kg/bag, 600kg/ pallet
- 3. 12MT/20GP', 24MT/40HQ'
- 4. Netural package available, OEM brand available
- 5. Store in cool and dry conditions

Shelf Life

The shelf life is 2 years. If over 2 years, please test and confirm the quality before using.