



# Technical Data Sheet

# Description

ACCURATE™5011N is a free-flowed and water-soluble white powder, produced by spray and dry process mostly based on Ethylene-Acetate(VAE). It dissolves in water easily and forms the membrane has excellent performance in increasing the cohesion, adhesion and flexibility of various sunstrates.

#### **Product Specifications**

GRADE	ACCURATE™5011N
Chemical name	Vinyl Acetate Ethylene Redispersible Powder
Solid Content	≥99%
Ash content(1000°C)	12±2 %
Packing density (g/l)	400-600
pH value	6.0-8.0
Particle size	90% pass 100 mesh
TG ( ℃)	15±5
Min Film-forming Temperature ( $^{\circ}$ C)	4
Flexibility	Rigid

#### **Recommend Applications**

Tile adhesive
Wall putty
Self-leveling mortar
Adhesive mortar for EIFS
Surface mortar for EIFS
Tile grout

## **Typical Properties**

Dissolves in water easily and forms emulsion quickly

Increase the adhesion to all kinds of substrates

Improve the sag resistance, workability, and anti-permeability for the materials

Good bonding strength

# Packing & Storage

- 1. Multi layer paper bag with inner PE film
- 2. 25kg/bag, 600kg/ pallet
- 3. 12MT/20GP', 24MT/40HQ'
- 4. Netural package available, OEM brand available
- 5. Store in cool, dry and clean conditions

### **Shelf Life**

The shelf life is 2 years. If over 2 years, please test and confirm the quality before using.