

Cellulose Ether (Landercoll™ EM200)

Hydroxyethyl Methyl Cellulose (HEMC/MHEC)

Technical Data Sheet

Description

LANDERCOLL™ EM200 is a non-ionic, water soluble cellulose ether, which offers a variety of functional properties when dissolve in water. It can be used as thickeners, protective colloids, suspending agents and water retention agents in many construction materials.

Product Specifications

Appearance:	white or off-white powder
Moisture content:	≤6 %
Residue on ignition:	≤5 %
pH value:	6.0-8.0
Particle size:	100% pass 80 mesh
Viscosity	185,000-215,000 mPa.s (NDJ-1, 2% solution, 20℃)
	65,000-80,000 mPa.s (Brookfield-RV, 2% solution, 20℃)

Recommend Applications

Tile adhesives
EIFS/EITCS
Skim coat/ wall putty

Typical Properties

1. Delayed solubility(surface treated): No	5. Water retention: high
2. Consistency development: very fast	6. Heat resistance: excellent
3. Final consistency: very high	7. Open time: long
4. Sag resistance: excellent	

Packing & Storage

1. Multi layer paper bag with inner PE film
2. 25kg/bag, 500 or 600kg/ pallet
3. 20' container: 10 Tons, 40' container: 22 Tons (with pallet)
4. Neutral or blank bag available, OEM brand available
5. Store in cool and dry conditions

Shelf Life

The shelf life is 2 years. If over 2 years, please test and confirm the quality before using.